



103z / 303z

ADJUSTABLE ZIPPER VEST (103Z)/
ADJUSTABLE ZIPPER VEST WITH LOOPS (303Z)

IMPORTANT INFO

- Meets FMVSS213 when used with 100SM and 100TM.
- For use by passengers weighing 31 -168lbs.
- Vests sized XS – M come with crotch straps meeting NHTSA guidelines.
- Portable crotch straps or sewn in straps are available to order for larger vests.
- An EZ-ON mount is needed to use this vest.
- 103Z compatible mounts include: 100SM, 100FM, 100WC.
- 303Z compatible mounts include: 100SM, 100FM, 100WC, 100TM.
- Register this transportation vest to be notified of a safety recall.
- Sizing (according to chest measurements)
XS 18” – 24” | S 25” – 32” | M 32” – 37” | L 37” – 43” | *Custom Sizing Available

WARRANTY

EZ-ON Products stands behind the products we make. Warranty covers any defects in material or workmanships under normal use during the warranty period. We will repair or replace product defects for 1 year from manufacturer date.

WARNING

Death or serious injury can occur If manufacturer’s instructions are not followed correctly. All EZ-ON products are dynamically tested to meet NHTSA standards. Please follow washing instructions on product tag. Replace product if it is damaged, frayed, or has been in a crash. Recommended replacement after six years. EZ-ON Products are not liable for injury if these recommendations are not followed.

PINCH TEST PROCEDURE

THE PINCH TEST

Tighten vest so that no pinch in the webbing can be achieved on the chest strap.
When vest is snug fingers will be unable to grab any webbing.



INCORRECT



CORRECT



103z / 303z

ADJUSTABLE ZIPPER VEST (103Z) (*Shown*) /
ADJUSTABLE ZIPPER VEST WITH LOOPS (303Z)

INSTALLATION INSTRUCTIONS



1. Hold vest while passenger steps into crotch straps with the E-Z-ON® parachute logo to front.
2. Choose one of the (3) zippers that fits child snugly. Be certain that the vest fits snugly.
3. Keep waist strap low around the hip level.
4. Adjust crotch straps to shorten or lengthen.
**To be snug but not tight.*
**A crotch strap is sewn onto all sizes except Large. For Large size continue to Step 5.*
5. Adjust shoulder straps using adjusters.
**Pull webbing through adjuster to reduce slack.*
**Do not pull too tight as this will cause vest to pull up off of hips.*
**The waist strap of the vest must stay low around the lap.*

KEY STEP

6. Back thread web through bar slides to lock.

PINCH TEST

Please refer to procedure on reverse side.